



Jowat-Toptherm®

237.50



Unfilled PO hot melt adhesive for edgebanding

- Facilitates thin, colorless bondlines
- Clean and easy processing
- High yield and bonding strength

The PO Benchmark for Edgebanding

Jowat-Toptherm® 237.50 is an unfilled edgebanding adhesive based on polyolefin (PO), characterized by high heat resistance, a wide range of adhesion and superior appearance of the adhesive joint. In comparison with conventional PO hot melt adhesives, this product achieves significantly higher bond strengths. **Jowat-Toptherm® 237.50** provides processors with a good alternative to PUR adhesives when a broad adhesion spectrum and a “zero bondline” are required. In many cases, investments in new machines are not necessary.

Jowat-Toptherm® 237.50 does not contain any fillers. This facilitates the manufacturing of virtually invisible, colorless adhesive joints, especially on dark decors and high-gloss furniture fronts, with an outstanding yield.

In addition, **Jowat-Toptherm® 237.50** is REACH-compliant and offers improved occupational safety compared to reactive adhesives with hazard labeling.

Jowat-Toptherm® 237.50

Unfilled PO hot melt adhesive for edgebanding

Based on	PO
Appearance	colorless
Processing temperature	190°C–210°C
Oxidation stability	● ● ●
Heat resistance	● ● ●
Water resistance	● ● ○
Feed speed	● ● ○
Yield	● ● ●

The information given in this leaflet is based on test results from our laboratories as well as on experience gained in the field, and does in no way constitute any guarantee of properties. Due to the wide range of different applications, substrates, and processing methods beyond our control, no liability may be derived from these indications nor from the information provided by our free technical advisory service. Before processing, please request the corresponding data sheet and observe the information in it! Customer trials under everyday conditions, testing for suitability at normal processing conditions, and appropriate fit-for-purpose testing are absolutely necessary. For the specifications as well as further information, please refer to the latest technical data sheets.