



Jowat
Classics

Jowatherm® 250.00



Powerful hot melt adhesive for attaching caps to beverage cartons

- **Unrivalled heat resistance**
- **For challenging surfaces**
- **Tried and trusted around the world**

Globally unmatched. For more than two decades.

Jowatherm® 250.00 has been established in the global market for nearly 25 years and has since become a tried and trusted partner for the closure of beverage cartons. To this day, the universal-purpose **Jowatherm® 250.00** continues to impress in processes with widely used applicators, surfaces and closure systems and has been adding value in the industry.

The manufacturing process is characterized by special conditions: fast cycle times, low application amounts coupled with the requirement for high initial strengths and good adhesion to the most different substrates are a prerequisite. Special attention in the development of **Jowatherm® 250.00** has been paid to its heat resistance, which has remained unmatched to this day.

Jowatherm® 250.00

Powerful hot melt adhesive for attaching caps to beverage cartons

Viscosity	at 190°C	~18,500 mPas
Processing temperature		180°C–210°C
Application method		nozzle, roller
Heat resistance		● ● ●
Cold resistance		● ● ○
Clean processing		● ● ○
Food safety		EU 10/2011; FDA 175.105; GB 9685
Remarks		approved by Tetra Pak and SIG Combibloc

The information given in this leaflet is based on test results from our laboratories as well as on experience gained in the field, and does in no way constitute any guarantee of properties. Due to the wide range of different applications, substrates, and processing methods beyond our control, no liability may be derived from these indications nor from the information provided by our free technical advisory service. Before processing, please request the corresponding data sheet and observe the information in it! Customer trials under everyday conditions, testing for suitability at normal processing conditions, and appropriate fit-for-purpose testing are absolutely necessary. For the specifications as well as further information, please refer to the latest technical data sheets.