



# Jowatherm-Reaktant® PUR Granulate



Easy entry into PUR technology

Processing on conventional edgebanders

Pull ring cans - perfect dosing

Easy change from EVA to PUR – and back

Different products available

Hot melt adhesives based on reactive polyurethane (PUR) currently represent the highest quality level in edgebanding. These moisture-curing hot melt adhesives require more caution during processing. They are supplied in moisture-proof packaging units and processed in special melting units protected from exposure to ambient humidity.

The newly available PUR in granulate form allows an easy entry into these kind of adhesives. The granulate form is not only interesting for proces-

sors new to the PUR hot melt technology, but above all also for small industrial companies that absolutely require PUR edgebanding for specific objects.

Jowat SE has developed a patented manufacturing method for moisture-reactive hot melt adhesives in granulate form. The tried and proven adhesives from the product family Jowatherm-Reaktant® are suitable for bonding regular edgebands of all kinds.

## Jowatherm-Reaktant®

For automatic edgebanders. Wide field of application, e.g. edges made of HPL/CPL, polyester, PVC, ABS, PP, resinated paper, solid wood or veneer.

		<b>608.00/01</b>	<b>607.50/51</b>
Polymer basis		PUR	PUR
Processing temperature	[°C]	approx. 120	approx. 140
Density	[g/cm³]	approx. 1.1	approx. 1.3
Viscosity processing temperature	[mPas]	approx. 80,000	approx. 75,000
Appearance		Transparent / white	Light beige / white

## INFO: Underwater granulation

In underwater granulation, the molten material to be granulated is extruded through the holes of a perforated plate into a cooling liquid (water in this case) and the string of extruded material is then cut off by fast rotating knives. The temperature difference between the hot adhesive and the cold water causes the adhesive string to contract instantly after it is cut off by the knives, leading to the typical ball shape of the underwater granulate. The round granules are characterised by an optimum flow behaviour and minimum contact surface, and therefore provide major benefits in dosing and dispensing compared to other geometries.



The information given in this leaflet is based on test results from our laboratories as well as on experience gained in the field, and does in no way constitute any guarantee of properties. Due to the wide range of different applications, substrates, and processing methods beyond our control, no liability may be derived from these indications nor from the information provided by our free technical advisory service. Before processing, please request the corresponding data sheet and observe the information in it! Customer trials under everyday conditions, testing for suitability at normal processing conditions, and appropriate fit-for-purpose testing are absolutely necessary. For the specifications as well as further information, please refer to the latest technical data sheets.